



DECLARATION OF PERFORMANCE

No. 007-CPR2013-05-14

1. Unique identification code of the product-type:

MULTISEAL 40 HOT APPLIED SEALANT

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Type: Hot Applied Sealant Type N2.

Batch / serial code: Product code HSBBC03

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Hot Applied Joint Sealants to be used in roads, airfields and other trafficked areas.
Also applicable to Hot Applied Joint Sealants in bituminous surfacing and between
bituminous surfacing and concrete pavements.**

CE marking has been affixed in accordance with the provisions of EN14188-1 Annex ZA

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

PPG Traffic Solutions (t/a Prismo Road Markings Ltd)

5 Drumhead Road

Chorley North Industrial Park

Chorley

Lancashire PR6 7BX

UK

Registered number 05906228

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

N/A

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP System 4



Traffic Solutions EMEA
5 Drumhead Road
Chorley North Industrial Park
Chorley, United Kingdom
PR6 7BX

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Determination of product type and verification of performance:

Test laboratory: GEOS Laboratories, Report number 59493, Report Date 27/08/2022

8. Declaration of performance concerning a construction product where ETA issued:
n/a

9. Declared performance

Essential characteristics	Performance	Technical specification
EN14188-1 product type: N2 Mandated Characteristics:		
Bond Strength - Clause 5.11	Table 2 Column 3	EN14188-1:2004
Cohesion - Clause 5.12	Table 2 Column 3	EN14188-1:2004
Watertightness - Clause 5.11	Table 2 Column 3	EN14188-1:2004
Resistance to Deformation - Clause 5.5, 5.6, 5.7, 5.8	Table 2 Column 3	EN14188-1:2004
Durability of bonding strength and watertightness in contact with asphalt pavements - Clause 5.10	Table 2 Column 3	EN14188-1:2004

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Gavin Newby (Technical Director PPG Traffic Solutions EMEA)